



Effect of Carrier to Noise Ratio threshold filtering on the long-term wind speed and Weibull distribution parameters for a pulsed heterodyne wind lidar

Gryning, Sven-Erik; Batchvarova, Ekaterina; Floors, Rogier Ralph; Pena Diaz, Alfredo

Published in:

Proceedings of 18th International Symposium for the Advancement of Boundary-Layer Remote Sensing

Publication date:

2016

Document Version

Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):

Gryning, S-E., Batchvarova, E., Floors, R. R., & Pena Diaz, A. (2016). Effect of Carrier to Noise Ratio threshold filtering on the long-term wind speed and Weibull distribution parameters for a pulsed heterodyne wind lidar. In *Proceedings of 18th International Symposium for the Advancement of Boundary-Layer Remote Sensing [V-2]*

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.



Effect of Carrier to Noise Ratio threshold filtering on the long-term wind speed and Weibull distribution parameters for a pulsed heterodyne wind lidar

Sven-Erik Gryning¹, Ekaterina Batchvarova², Rogier Floors¹, Alfredo Peña¹

¹ *DTU Wind Energy, Risø Campus, Technical University of Denmark, Roskilde, Denmark*

² *National Institute of Meteorology and Hydrology, Sofia, Bulgaria*

Wind speed observations from tall towers are used in combination with observations up to 600 m in altitude from a pulsed heterodyne Doppler wind-lidar (Leosphere WLS70) to study the long-term wind profile over sub-urban, coastal-rural and marine areas.

When the Doppler wind-lidar Carrier to Noise Ratio (CNR) is lower than a threshold value (typically - 22 dB) the observations are often not used as the uncertainty in the wind speed measurements has increased above a certain value. Here we discuss some consequences of the filtering on the on measured long-term wind speed and Weibull distribution parameters. The analysis shows that the mean wind speed is a function of the applied CNR threshold, since the CNR is a direct consequence of the atmospheric aerosol and dust concentration driven by changes in near-surface wind speed.

For concurrent and complete profiles, i. e. profiles which have a CNR larger than a given threshold at all measuring levels up to 600m, use of the traditional -22 dB CNR threshold value results in a ~7% over-prediction of the long term mean wind speed over land, and a ~12% over-prediction in coastal and marine environments. In addition, the height of the maximum in the profile of the shape parameter of the Weibull distribution (so-called reversal height) was found to depend on the applied CNR threshold; it is found to be lower at small CNR threshold values.

When the wind-lidar measurements were filtered with the same CNR threshold at 100 m only, the effect on the wind speed was less, being a 1% over-prediction over land and 7% over-prediction in coastal and marine areas.